



ID.	SPEC	LENGTH	A	B	C
E4098G-1	APWA 311	36 IN	1 $\frac{1}{4}$ IN	33 $\frac{1}{2}$ IN	1 $\frac{3}{4}$ IN
E4098G-2	APWA 311	44 IN	1 $\frac{1}{4}$ IN	33 $\frac{1}{2}$ IN	1 $\frac{3}{4}$ IN
E4098G-3	APWA 311	64 IN	1 $\frac{1}{4}$ IN	33 $\frac{1}{2}$ IN	1 $\frac{3}{4}$ IN
E4098G-4	D74A GT1	34 IN	7 $\frac{1}{16}$ IN	13 $\frac{1}{8}$ IN	1 $\frac{7}{8}$ IN
E4098G-5	D74A GT2	46 IN	7 $\frac{1}{16}$ IN	13 $\frac{1}{8}$ IN	1 $\frac{7}{8}$ IN
E4098G-6	D74A GT3	34 IN	7 $\frac{5}{8}$ IN	18 $\frac{3}{4}$ IN	1 $\frac{7}{8}$ IN
E4098G-7	D74A GT4	46 IN	7 $\frac{5}{8}$ IN	18 $\frac{3}{4}$ IN	1 $\frac{7}{8}$ IN
E4098G-8	D74A GT4	44 IN	6 $\frac{5}{8}$ IN	20 $\frac{5}{8}$ IN	1 $\frac{3}{4}$ IN

E2020 E2060

NOTES:
 ONE REQUIRED FOR GT3 @34"
 MATERIAL: STEEL ASTM A-36
 FINISH: HOT DIP GALVANIZED ASTM A123

W5x19 SUPPORT BEAM



SOUTH BAY FOUNDRY
 STEEL DIVISION
 9444 ABRAHAM SANTEE, CA 92071, USA.

PHONE(619)956-2780 FAX(619)956-2788

APPROVAL DATE:

DRAWN BY: BE

WT. 19 LB./FT

I.D.# E4098G

APPROVED BY:

SCALE: NTS

DATE: 03/01/11

SHEET: 10F1